


Produits > Hydraulique > Raccords > JIC 37°

Coude orientable



Référence	Tube O.D.	Dimension D	Dimension H (Hex)	Dimension h (Hex)	Dimension H1 (Hex)	Dimension L	Dimension L1	Dimension L2	Dimension L3	Material	Unified National Fir
FSL-2T-S316	1/8 in 3 mm	1.6 mm	9.5 mm	11.1 mm	11.1 mm	27.4 mm	19.6 mm	24.6 mm	16.7 mm	316 Stainless Steel	5/16"-24
FSL-3T-S316	3/16 in 4 mm	3.2 mm	11 mm	11.1 mm	12.7 mm	30.5 mm	21.1 mm	25.4 mm	17.1 mm	316 Stainless Steel	3/8"-24
FSL-4T-S316	1/4 in 6.0 mm	4.4 mm	14.2 mm	11.1 mm	14.2 mm	31.7 mm	22.6 mm	25.4 mm	16.7 mm	316 Stainless Steel	7/16"-20
FSL-5T-S316	5/16 in 8.0 mm	6.0 mm	16.0 mm	14.3 mm	15.8 mm	34.5 mm	24.1 mm	26.9 mm	17.4 mm	316 Stainless Steel	1/2"-20
FSL-6T-S316	3/8 in 10.0 mm	7.5 mm	17.4 mm	14.3 mm	17.4 mm	38.8 mm	26.9 mm	31.8 mm	22.3 mm	316 Stainless Steel	9/16"-18
FSL-8T-S316	1/2 in 12.0 mm	9.9 mm	22.2 mm	19.0 mm	22.2 mm	44.50 mm	31.8 mm	35.1 mm	24.4 mm	316 Stainless Steel	3/4"-16
FSL-10T-S316	5/8 in 16.0 mm	12.3 mm	25.4 mm	22.2 mm	25.4 mm	53.40 mm	36.8 mm	41.1 mm	28.4 mm	316 Stainless Steel	7/8"-14

Référence	Tube O.D.	Dimension D	Dimension H (Hex)	Dimension h (Hex)	Dimension H1 (Hex)	Dimension L	Dimension L1	Dimension L2	Dimension L3	Material	Unified National Fit
FSL-12T-S316	3/4 in 18 mm 20 mm	15.5 mm	32.0 mm	27.0 mm	31.7 mm	57.7 mm	42.2 mm	44.4 mm	30.1 mm	316 Stainless Steel	1 1/16"-12
FSL-14T-S316	7/8 in 22 mm	18 mm	35.0 mm	33.3 mm	34.9 mm	63.3 mm	45.7 mm	45.2 mm	30.5 mm	316 Stainless Steel	1 3/16"-12
FSL-16T-S316	1 in 25 mm	21.5 mm	38.0 mm	33.3 mm	38.1 mm	65.0 mm	46.0 mm	50.8 mm	35.7 mm	316 Stainless Steel	1 5/16"-12
FSL-20T-S316	1 1/4 in 32 mm	37.5 mm	50.8 mm	41.3 mm	50.8 mm	70.8 mm	52.3 mm	58.7 mm	42.8 mm	316 Stainless Steel	1 5/8"-12
FSL-24T-S316	1 1/2 in 38 mm	33.0 mm	57.1 mm	47.6 mm	57.1 mm	85.9 mm	59.2 mm	65.8 mm	47.2 mm	316 Stainless Steel	1 7/8"-12
FSL-32T-S316	2 in 50 mm	45.0 mm	73 mm	63.5 mm	69.8 mm	105.2 mm	77.7 mm	85.9 mm	62.1 mm	316 Stainless Steel	2 1/2"-12